

# TIRE DRESSING

## SOLVENT AND SILICONE DRESSING

PRODUCT CODE: 150

### DESCRIPTION AND PRODUCT BENEFITS:

TIRE DRESSING is a superior V.O.C. Compliant dressing, which emits a pleasant scent. TIRE DRESSING is simple to apply, levels quickly and leaves a lasting wet-look shine. Use TIRE DRESSING on tires, mouldings, bumpers, vinyl trim, and vinyl tops to display a best-dressed appearance. Long-lasting and water repellent, TIRE DRESSING is ideal for North American weather.

### DIRECTIONS OF USE AND APPLICATION:

1. Pre-clean the areas of application to ensure dust, dirt, and grime is removed. 2. Apply TIRE DRESSING with a solvent resistant trigger sprayer or a dedicated soft cloth applicator. 3. Allow TIRE DRESSING to dry or wipe down with a soft, clean lint-free rag. *Tips: Do not dilute the product, use as is.*

### PRECAUTIONS:

Sling-off from freshly dressed tires may cause permanent staining of some plastic panels; DO NOT DRIVE THE VEHICLE UNTIL EXCESS HAS BEEN WIPED OFF, especially where the tire contacts the rim. Dressing alone will not cause staining. TIRE DRESSING can make surfaces slippery. DO NOT APPLY TO SEATS, STEERING WHEEL, OR FOOT CONTROLS. Do not mix with other chemicals. Keep from freezing.

### HEALTH & SAFETY INFORMATION:

For further information on the safe handling, storage and precautions for use of this product, consult the Safety Data Sheet. Keep out of reach of children.

### DISCLAIMER:

As the actual conditions of use are out of our control no liability is accepted for any loss or damage caused directly or indirectly through the use of our products. Intending users should satisfy themselves, by carrying out appropriate tests, as to the suitability of this product for any particular purpose.



### TYPICAL DATA:

**APPEARANCE:** Clear blue liquid.  
**SPECIFIC GRAVITY:** ~ 0.80 g/ml  
**ODOUR:** Mulberry.  
**SOLUBILITY:** Insoluble in water.  
**% NON-VOLATILE:** ~ 30.0  
**VISCOSITY:** Water thin.  
**FLASH POINT:** ~ 51°C

### AVAILABLE SIZES:



A15012 - **JUG** - 3.78 L / 1 US GAL  
 A15014 - **CUBE** - 18.9 L / 5 US GAL  
 A15016 - **KEG** - 56.8 L / 15 US GAL  
 A15018 - **DRUM** - 208.2 L / 55 US GAL  
 BA150 - **WORKPLACE LABEL**

